

## Sylspot Black

SYLSPOT KIT ROUND 345LM 830 ADJ IP20 BLK  
0005737



### Product features

- Recessed spotlight Kit with RefLED GU10 LED spotlight lamp Ø50mm. Polycarbonate body, round bezel ring in black finish, vertical tilt 30°, IP20 degree of protection, class II. Lumen output 345lm, CCT 3000K, beam angle 36°, power 4,5W, efficacy 77 lm/W, lifetime 15.000h. Outer dimensions: Ø90x103mm, cut-out Ø70-75mm. Suitable for internal environment only and for LED lamps only.



## PRODUCT OVERVIEW

Product name	SYLSPOT KIT ROUND 345LM 830 ADJ IP20 BLK
Technology	LED (replaceable lamp)
Housing	PC Polycarbonate
Mount	Ceiling recessed mounting
Environment	Indoor
General application	Residential & Consumer
ETIM Class	EC001744
Warranty	3 years
Fixture luminous flux (lm)	345
Luminaire efficacy (lm/W)	77
Colour temperature (K)	3000
Light colour	Warm White
CRI (Ra)	80
Colour Variation Initial (SDCM)	SDCM6
Beam Angle (°)	36
Photobiological Risk Group	RG1
Total power consumption (W)	4.5
Electrical protection	Class II
Dimmable	No
Housing colour	Black
IP rating	IP20
IK rating	IK03
Product EAN number	5410288057378
Light source included	0028433

## DATA TABLE

### General data

Product name	SYLSPOT KIT ROUND 345LM 830 ADJ IP20 BLK
Technology	LED (replaceable lamp)
Housing	PC Polycarbonate
Mount	Ceiling recessed mounting
Environment	Indoor
General application	Residential & Consumer

## Sylspot Black

SYLSPOT KIT ROUND 345LM 830 ADJ IP20 BLK  
0005737

ETIM Class	EC001744
Warranty	3 years

### Optical data

Fixture luminous flux (lm)	345
Luminaire efficacy (lm/W)	77
Colour temperature (K)	3000
Colour Code	830
Light colour	Warm White
CRI (Ra)	80
Colour Variation Initial (SDCM)	SDCM6
Beam Angle (°)	36
Photobiological Risk Group	RG1

### Electrical data

Total power consumption (W)	4.5
Mains voltage (V)	220-240V~
Electrical protection	Class II
Dimmable	No
Inrush Current (A)	10
Inrush Duration (µs)	150
Glow Wire Test (°C)	650
Nominal Frequency (Hz)	50/60Hz
Max. Luminaires per 10A C Breaker	100
Max. Luminaires per 13A C Breaker	130
Max. Luminaires per 16A C Breaker	160
Max. Luminaires per 20A C Breaker	200

### Lifetime data

Lifespan L70 B50	15000
------------------	-------

### Physical data

Housing colour	Black
IP rating	IP20
IK rating	IK03
Nominal Product Length (mm)	90
Nominal Product Width (mm)	90
Nominal Product Height (mm)	85
Nominal Product Diameter (mm)	90
Weight (kg)	0.09

### Packaging



Single packaging type	Carton
Product EAN number	5410288057378
Packaging single length / height (cm)	9.0
Packaging single width (cm)	7.5
Packaging single depth (cm)	11.5
DUN14 (outer)	15410288057375
Units per outer package	40

## Sylspot Black

SYLSPOT KIT ROUND 345LM 830 ADJ IP20 BLK  
0005737

Packaging outer length / height (cm)	39.9
Packaging outer width (cm)	38.2
Packaging outer depth (cm)	25.3

### PHOTOMETRY



### TECHNICAL DRAWINGS

