

### ToLEDo Retro Ball ToLEDo RT BALL V4 CL 250LM 827 E27 SL 0027240



#### **Product features**

• Perfect for decorative and general lighting applications and creates a warm ambience similar to traditional lamps. The versatile ToLEDo Retro ball range is the ideal replacement for halogen and incandescent lamps and perfect for chandeliers and decorative applications. Same look, size and functionality as incandescent lamps• Omni-directional light distribution• A++ energy rating• Gives same sparkling light effect as the incandescent lamp• Dimensionally identical to incandescent lamps - fits all fixtures • Environment-friendly - no mercury and lower CO2 emissions









### PRODUCT OVERVIEW

Product name	ToLEDo RT BALL V4 CL 250LM 827 E27 SL
Technology	LED
Watt (Rated) (W)	2.5
Туре	ToLEDo Retro Ball
Cap/Base	E27
Fixture rating	Open
General application	Hospitality, Residential & Consumer
ETIM Class	EC001959
E-number FI	4740422
E-number SE	8295048
Warranty	3 years
Luminous flux (lm)	250
Colour temperature (K)	2700
Light colour	Homelight
CRI (Ra)	80
Beam Angle (°)	300
Wattage (W)	2.5
Product Voltage (V)	230
Average life (Nominal) (h)	15000
Product EAN number	5410288272405

#### **DATA TABLE**

General data	
Product name	ToLEDo RT BALL V4 CL 250LM 827 E27 SL
Technology	LED
Watt (Rated) (W)	2.5
Туре	ToLEDo Retro Ball
Cap/Base	E27
Fixture rating	Open
General application	Hospitality, Residential & Consumer
Performance ambient temperature Tq (°C)	25
ETIM Class	EC001959
E-number FI	4740422



# ToLEDo Retro Ball ToLEDo RT BALL V4 CL 250LM 827 E27 SL 0027240

E-number SE	8295048
Warranty	3 years
Optical data	
Luminous flux (Im)	250
Luminous flux (Rated) (Im)	250
Colour temperature (K)	2700
Light colour	Homelight
CRI (Ra)	80
Beam Angle (°)	300
Lumen maintenance at end of nominal life (%)	70
Electrical data	
Wattage (W)	2.5
Equivalent watt (W)	25
Starting time (max) (s)	0.5
Warm-up time to 60% of full light (max) (s)	1
Product Voltage (V)	230
Lamp power factor	0.5
No. Of switching cycles before premature failures	>50000
Inrush Current (A)	1.2
Nominal Frequency (Hz)	50/60Hz
Max. Luminaires per 10A C Breaker	83
Max. Luminaires per 16A C Breaker	133
Max. Luminaires per 20A C Breaker	167
Lifetime data	
Average life (Nominal) (h)	15000
Average life (Rated) (h)	15000
Physical data	
Nominal Product Length (mm)	78
Nominal Product Diameter (mm)	70
Weight (kg)	45
TTOISTIT (NS)	
	45
Packaging	45
	45 0.019
Packaging Single packaging type	45 0.019 Carton
Packaging Single packaging type Product EAN number	45 0.019 Carton 5410288272405
Packaging Single packaging type Product EAN number Packaging single length / height (cm)	45 0.019 Carton 5410288272405 9.8
Packaging Single packaging type Product EAN number Packaging single length / height (cm) Packaging single width (cm)	45 0.019 Carton 5410288272405 9.8 4.8
Packaging Single packaging type Product EAN number Packaging single length / height (cm) Packaging single width (cm) Packaging single depth (cm)	45 0.019 Carton 5410288272405 9.8 4.8 4.8
Packaging Single packaging type Product EAN number Packaging single length / height (cm) Packaging single width (cm) Packaging single depth (cm) DUN14 (inner)	45 0.019 Carton 5410288272405 9.8 4.8 4.8 25410288272409
Packaging Single packaging type Product EAN number Packaging single length / height (cm) Packaging single width (cm) Packaging single depth (cm) DUN14 (inner) Units per inner package	45 0.019 Carton 5410288272405 9.8 4.8 4.8 25410288272409 6
Packaging Single packaging type Product EAN number Packaging single length / height (cm) Packaging single width (cm) Packaging single depth (cm) DUN14 (inner) Units per inner package Packaging inner length / height (cm)	45 0.019 Carton 5410288272405 9.8 4.8 4.8 25410288272409 6 15.3



## ToLEDo Retro Ball ToLEDo RT BALL V4 CL 250LM 827 E27 SL 0027240

Units per outer package	60
Packaging outer length / height (cm)	54.7
Packaging outer width (cm)	33.1
Packaging outer depth (cm)	14.0
,	

### Safety data

Breakage cleaning instructions	Not applicable
Special purpose lamp	No
Dry applications use only	Yes
Suitable for household illumination	Yes
Safety message	Not Suitable for totally enclosed fixtures

## TECHNICAL DRAWINGS

