

Filler F10/F20 Premium

Version: jan-18

Filler F10/F20 Premium is a natural primer with graphene technology for Graphenstone® white paint. It allows to regulate the texture of the substrate, to cover micro-cracks (< 1 mm) and to homogenize repaired or scraped surfaces of old paint. There are two types regarding to granularity.

PRODUCT DESCRIPTION

Features:

Filler F10: with a granulometry of little particles.
 Filler F20: with a granulometry of thicker particles.
 Regulates the support's absorption and texture.
 Homogenizes the surface.
 Helps to save material and labour.
 Excellent covering power and adherence.
 Absorbs CO₂.
 Contains high quality lime and graphene fibres.
 Breathable. Avoids condensation.
 High adherence. Tough and long-lasting.
 Suitable for exterior and interior.
 Free of VOCs and formaldehyde emissions.
 Cradle to Cradle Certified™ GOLD.
 GreenRate Certified™ LEVEL A

Technical properties:

Specific weight	1.45 ± 0.05 g/cm ³
pH	12.5 ± 1
Viscosity	[90 - 130] U.K.
Solid content	65 ± 5 %
Permeability to water vapour (EN 1062-1)	Class 1 S _D < 0.14 m
Capillary water absorption	w < 0.01 kg/m ² ·h ^{0.5}
Fire performance	A1
Nature	Aerated lime
Appearance	Dense liquid
Finish	Matte
VOC content	< 1 g/l
VOC emission	Class A+

Yield:

5-7 m²/l (1 coat). It depends on the type and condition of the substrate. The exact consumption must be determined by the means of a sampling of the work.

Format:

Available in pots of 1 l, 4 l, 12.5 l, 15 l.

Storage:

Keep in original pack, closed and in a cool and dry place. Keep from freezing and avoid direct sun exposure. Unopened, it may be conserved for at least 12 months from the date of manufacture. The product may thicken without losing its properties; shake well before use

APPLICATINO INSTRUCTIONS

Application surfaces:

It can be applied on all types of surfaces common in construction: mortar, brick, concrete, old paintins, etc.

Conditions of the substrate:

The substrate must be dry, firm, well-adhered and free from any impurities that may hinder the product from setting fully.

Preparation of the substrate:

If the substrate presents algae, mold, fungi and / or other impurities, it is recommended to do a thorough cleaning, eliminating in its entirety and with specific products for this purpose.

If the substrate has salt deposits, brush and apply *Neutralysal Premium*.

If the substrate contains a high moisture level, apply *StopWater Premium* diluted 1:1 with water and paint 24 hours before its application.

If the substrate presents scaling/blistering of the existing paint, first remove areas that do not adhere by scraping and brushing.

If the substrate presents surface cracks, the recommendation depends on the width of the crack:

1-3 mm	Apply <i>Füllmasse Premium</i> (with a fiberglass mesh if >1 mm).
3-10 mm	Chip superficially and apply <i>Naturglue Premium</i> with mesh
>10 mm	Requires architectural assessment.

If the substrate presents deterioration of mortar, first remove areas that do not adhere by scraping or pricking and clean up by brushing or plenty of water. The recommendation depends on the damaged depth:

< 3 mm	Apply <i>Ecoputty Premium</i> .
3-8 mm	Apply <i>Naturglue Premium</i> with mesh.
8-20 mm	Apply <i>MortarBase Premium</i> and finish with <i>MortarFine Premium</i> (<10 mm) with mesh.
>20 mm	Apply <i>Naturglue Premium</i> (5 mm), apply tile according to width of the cavity (1-5 cm) and apply <i>Naturglue Premium</i> (<10 mm) with a mesh.

If the substrate presents pathology such as structural cracks, moisture by capillarity, condensation or filtration, etc.; then it is necessary to resolve the structural problems first.

Depending upon the nature of the substrates, the previous actions vary as follows:

- Old glossy paint or putty: clean surfaces and sand slightly.
- Very absorbent substrates (clay, adobe, rammed earth, etc.): apply *Minerseal Premium*.
- If the substrate is wood or metal (without corrosion or oxidation) or without porosity: apply *Four2Four Premium*.

Product preparation:

Stir and dilute with water to 10-15% of the product weight (150-200 ml of water per liter of product approx.), ensure a homogeneous mixture. Avoid excessive shaking to minimize bubble occlusion.

Application method:

Apply one coat evenly. Paint in sections starting with the borders. Do not paint on areas that are drying, avoid overlapping. An excess of product can generate micro-cracks.

Drying:

In conditions of 25 °C and 60% relative humidity: 4-6 hours to apply Graphenstone® natural white paint.

Environmental conditions:

The work temperature (environment and support) must be between +5 °C and +40 °C. Do not apply in direct sunlight or on supports heated by the sun.

Tools:

Roller, brush, airless or other type of projection only for *Filler F10 Premium*.

Airless application:

Spray angle: 30°
 Spray distance: 50-60 cm
 Tip size: 0.027 in.
 Minimum machine power: 1750 W
 Machine filter: 30-40 mesh.

Tool cleaning:

Clean tools after use with warm water.

Notes

The mineral substrate must be at least 28 days old.

The substrates to be painted must be resistant to high alkalinity.

Do not apply to surfaces in constant contact with water.

In case of rain, let the substrate dry before applying. It is recommended to protect the treated surface from rain until its later painting.

The parts that are not going to be treated must be protected (glass, wood, etc.).

Should there be strict aesthetic requirements, it is recommended to perform prior tests.

Do not mix with other products or specific properties may change.

Complementary products:

It is recommended to use the *Graphenstone®* product line for complementary actions, according to the required application, repair and/or finish. Please, refer to the relevant Technical Data Sheets.

DECLARATIONS

The manufacturer declares that the composition of the product, it does not contain hazardous substances and it is free of VOC emissions.

For more information, please refer our website:
<http://graphenstone.com/Graphenstone-Global-Certificados.html>

ADDITIONAL INFORMATION

Usage warnings:

None in particular for normal use and people who do not have special pathologies. Alkaline product, protect skin and eyes especially. Apply with good ventilation, do not inhale product. Keep out of reach of children.

Waste management:

According to local legal provisions. The pots are made of polypropylene. Help protect the environment, do not throw waste through the drain and use the nearest recycling centre.

Responsible gesture:

Minimize the product waste by estimating the amount you will need. Recover the unused mortar to give it a new use, keep it under the Storage section.

Safety information:

For information regarding safety, physical, ecological and toxicological information see the latest version of the product's Material Safety Data Sheet.

Technical substrate:

For further information, please contact with local distributor or manufacture:
technicalsupport@graphenstone.com

The information provided is given in good faith, based on current knowledge and IEdiSA's experience with the products when they are properly stored, handled and applied in normal situations and in accordance with the recommendations of IEdiSA. The Technical Specifications sheet is useful for information and consulting but is not legally binding. In particular, it does not exempt the user from testing and verifying the suitability of the product for the desired application and purpose. IEdiSA reserves the right to modifications that improve the product or its application. This version invalidates previous ones