

## TOLEDO CANDLE DIMMABLE

ToLEDo CAND V4 DIM FROSTED 470LM E14 SL

0026935



### Product features

- Compact and elegant design
- Suitable replacement for halogen, incandescent and compact fluorescent candle lamps
- Instant light at the flick of a switch
- Uniform light distribution
- Good colour rendering (CRI 80)
- Dimmable with approved dimmers
- Perfect for hotels, restaurants, lobbies, corridors, stairwells, reception areas
- Lower maintenance costs
- A+ energy rating



### PRODUCT OVERVIEW

|                            |   |
|----------------------------|---|
| IPC Code                   | 0026935   |
| Product name               | ToLEDo CAND V4 DIM FROSTED 470LM E14 SL         |
| Technology                 | LED   |
| Watt (Rated) (W)           | 5.6   |
| Cap/Base                   | E14   |
| Fixture rating             | Open  |
| General application        | Hospitality, Education, Residential & Consumer, |
| ETIM Class                 | EC001959  |
| E-number FI                | 4740197   |
| E-number SE                | 8296540   |
| Luminous flux (lm)         | 470   |
| Colour temperature (K)     | 2700  |
| Light colour               | Homelight                                       |
| CRI (Ra)                   | 80  |
| Wattage (W)                | 5.6   |
| Product Voltage (V)        | 230   |
| Dimmable                   | Yes   |
| Average life (Nominal) (h) | 15000   |
| Product EAN number         | 5410288269351                                   |

### DATA TABLE

#### General data

|                     |   |
|---------------------|---|
| IPC Code            | 0026935   |
| Product name        | ToLEDo CAND V4 DIM FROSTED 470LM E14 SL         |
| Technology          | LED   |
| Watt (Rated) (W)    | 5.6   |
| Cap/Base            | E14   |
| Fixture rating      | Open  |
| General application | Hospitality, Education, Residential & Consumer, |
| ETIM Class          | EC001959  |
| E-number FI         | 4740197   |

## TOLEDO CANDLE DIMMABLE

*ToLEDo CAND V4 DIM FROSTED 470LM E14 SL*

0026935

E-number SE 8296540

### Optical data

|                            |           |
|----------------------------|-----------|
| Luminous flux (lm)         | 470       |
| Luminous flux (Rated) (lm) | 470       |
| Colour temperature (K)     | 2700      |
| Light colour               | Homelight |
| CRI (Ra)                   | 80        |
| Beam angle (Rated) (°)     | 280       |

### Electrical data

|   |           |
|---|-----------|
| Wattage (W)                                       | 5.6       |
| Starting time (max) (s)                           | <0.5      |
| Warm-up time to 60% of full light (max) (s)       | <1.0      |
| Mains voltage (V)                                 | 220-240V~ |
| Product Voltage (V)                               | 230       |
| Lamp power factor                                 | 0.5       |
| No. Of switching cycles before premature failures | 50000     |
| Dimmable  | Yes       |
| Lamp Energy Label (class)                         | A+        |
| kWh per 1000 hours burning time                   | 6         |
| Nominal Frequency (Hz)                            | 50/60Hz   |

### Lifetime data

|   |       |
|---|-------|
| Performance ambient temperature Tq (°C) | 25    |
| Average life (Nominal) (h)              | 15000 |
| Average life (Rated) (h)                | 15000 |

### Physical data

|                               |       |
|-------------------------------|-------|
| Nominal Product Length (mm)   | 110   |
| Nominal Product Diameter (mm) | 38    |
| Weight (kg)                   | 0.041 |

### Packaging

|                                       |                |
|---------------------------------------|----------------|
| Single packaging type                 | Carton         |
| Product EAN number                    | 5410288269351  |
| Packaging single length / height (cm) | 12.5           |
| Packaging single width (cm)           | 4.8            |
| Packaging single depth (cm)           | 4.8            |
| DUN14 (outer)                         | 15410288269358 |
| Units per inner package               | 6              |
| Packaging inner length / height (cm)  | 15.0           |
| Packaging inner width (cm)            | 10.5           |
| Packaging inner depth (cm)            | 15.3           |
| Units per outer package               | 60             |
| Packaging outer length / height (cm)  | 55.2           |
| Packaging outer width (cm)            | 17.6           |

## TOLEDO CANDLE DIMMABLE

ToLEDo CAND V4 DIM FROSTED 470LM E14 SL

0026935

Packaging outer depth (cm) 33.6

### Safety data

|                                     |  |
|-------------------------------------|--|
| Breakage cleaning instructions      | Not applicable                             |
| Special purpose lamp                | No   |
| Intended purpose                    | No   |
| Dry applications use only           | Yes  |
| Suitable for household illumination | Yes  |
| Safety message                      | Not Suitable for totally enclosed fixtures |

