

## ToLEDo GLS DIMMABLE

ToLEDo GLS V5 DIM 806LM 827 E27 SL

0028510



### Product features

- Compact and elegant design
- Suitable replacement for halogen, incandescent and compact fluorescent GLS lamps
- Instant light at the flick of a switch
- Uniform light distribution
- Good colour rendering (CRI 80)
- Dimmable with approved dimmers
- Perfect for hotels, restaurants, lobbies, corridors, stairwells, reception areas
- Lower maintenance costs
- A+ energy rating



## PRODUCT OVERVIEW

IPC Code	0028510
Product name	ToLEDo GLS V5 DIM 806LM 827 E27 SL
Technology	LED
Watt (Rated) (W)	8.5
Cap/Base	E27
Fixture rating	Open
General application	Hospitality, Residential & Consumer
ETIM Class	EC001959
E-number FI	4740835
Luminous flux (lm)	806
Colour temperature (K)	2700
Light colour	Homelight
CRI (Ra)	80
Wattage (W)	8.5
Product Voltage (V)	230
Average life (Nominal) (h)	15000
Product EAN number	5410288285108

## DATA TABLE

### General data

IPC Code	0028510
Product name	ToLEDo GLS V5 DIM 806LM 827 E27 SL
Technology	LED
Watt (Rated) (W)	8.5
Cap/Base	E27
Fixture rating	Open
General application	Hospitality, Residential & Consumer
ETIM Class	EC001959
E-number FI	4740835

### Optical data

Luminous flux (lm)	806
Luminous flux (Rated) (lm)	806

## ToLEDo GLS DIMMABLE

ToLEDo GLS V5 DIM 806LM 827 E27 SL  
0028510

Colour temperature (K)	2700
Light colour	Homelight
CRI (Ra)	80
Lumen maintenance at end of nominal life (%)	70

### Electrical data

Wattage (W)	8.5
Equivalent watt (W)	60
Starting time (max) (s)	0.5
Warm-up time to 60% of full light (max) (s)	1
Product Voltage (V)	230
Lamp power factor	0.9
No. Of switching cycles before premature failures	50000
Inrush Current (A)	4
Lamp Energy Label (class)	A+
kWh per 1000 hours burning time	9
Nominal Frequency (Hz)	50/60Hz
Max. Luminaires per 10A C Breaker	103
Max. Luminaires per 16A C Breaker	166
Max. Luminaires per 20A C Breaker	208

### Lifetime data

Performance ambient temperature Tq (°C)	25
Average life (Nominal) (h)	15000
Average life (Rated) (h)	15000

### Physical data

Nominal Product Length (mm)	112
Nominal Product Diameter (mm)	60
Weight (kg)	0.056

### Packaging

Single packaging type	Carton
Product EAN number	5410288285108
Packaging single length / height (cm)	11.3
Packaging single width (cm)	6.4
Packaging single depth (cm)	6.4
DUN14 (outer)	15410288285105
Units per inner package	6
Packaging inner length / height (cm)	20.4
Packaging inner width (cm)	13.4
Packaging inner depth (cm)	13.7
DUN14 (inner)	25410288285102
Units per outer package	60
Packaging outer length / height (cm)	72.4
Packaging outer width (cm)	22.2

## ToLEDo GLS DIMMABLE

ToLEDo GLS V5 DIM 806LM 827 E27 SL

0028510

Packaging outer depth (cm)	29.7
----------------------------	------

### Safety data

Breakage cleaning instructions	Not applicable
Special purpose lamp	No
Intended purpose	No
Dry applications use only	Yes
Suitable for household illumination	Yes
Safety message	Not Suitable for totally enclosed fixtures

